


Floor-Standing (R410A)

Specifications

- Built-in electronic expansion valve (EEV) for refrigerant flow control (2000-step).
- 'Silent' operation (sound pressure at low fan speed: 30-32 dB(A)).
- Long-life washable permanent filter.

- Auto Restart function.



Indoor Unit			AC100KNPDEH/EU	AC140KNPDEH/EU
Outdoor Unit - Mono-Phase			AC100KXADEH/EU	-
Outdoor Unit - Tri-Phase			-	AC140KXADGH/EU
Capacity				
Cooling	Cooling (Min/Nominal/Max)	kW	3.5/10.0/12.3	4.2/13.4/16.7
	Heating up to +7 °C (Min/Nominal/Max)	kW	4.2/11.2/14.0	4.0/15.5/20.0
	Heating @ -5 °C	kW	11.00	15.20
	Heating @ -15 °C	kW	9.60	13.5
Performance				
Energy Efficiency Cooling	SEER ¹	W/W	5.8/ A+	-
	Power Consumption	kWh/a	603	-
	Pdesignc	kW	10.0	-
	EER	W/W	2.7	3.1
Energy Efficiency Heating	SCOP ¹	W/W	4.1/ A+	-
	Power Consumption	kWh/a	1,810	-
	Pdesignh (average)	kW	5.3	-
	COP ¹	W/W	3.30	3.44
Airflow Rate	Indoor Unit (H/M/L)	m ³ /min	29.0	35.5
Sound Power	Indoor Unit	dB(A)	60	63
	Outdoor Unit	dB(A)	70	70
Sound Pressure	Indoor Unit (H/M/L)	dB(A)	47/44/41	51/48/45
	Outdoor Unit (H/L)	dB(A)	55/53	54/53
Fan/Outdoor Unit	Type		Sirocco	Sirocco
	Power	W	97	154
	Number of Fans		1	1
External Static Pressure	Min/Std/Max	Pa		
Operating Temperature Range	Cooling	°C	-15-50	-15-50
	Heating	°C	-20.0-24.0	-20.0-24.0
Electrical Data				
Power Source	Indoor Unit	Φ, #, V, Hz	1Φ, 2, 220-240 V, 50 Hz	1Φ, 2, 220-240 V, 50 Hz
	Outdoor Unit Mono-Phase	Φ, #, V, Hz	1Φ, 2, 220-240 V, 50 Hz	3Φ, 4, 380-415 V, 50 Hz
	Outdoor Unit Tri-Phase	Φ, #, V, Hz		
Compressor Type	Outdoor Unit	Type	Twin BLDC Rotary	Twin BLDC Rotary
Power (Min/Nominal/Max)	Cooling	kW	1.10/3.70/4.90	0.90/4.32/5.90
	Heating	kW	0.90/3.39/4.50	0.70/4.50/6.60
Current Input	Cooling (Min/Std/Max)	A	4.3/16.4/23.2	1.9/6.8/9.5
	Heating (Min/Std/Max)	A	4.1/14.9/20.5	1.4/6.7/10.7
	Cooling - Tri-Phase (Min/Std/Max)	A		
	Heating - Tri-Phase (Min/Std/Max)	A		
Dimensions				
Net Dimensions (W x H x D)	Indoor Unit	mm	610 x 1,850 x 400	610 x 1,850 x 400
	Outdoor Unit	mm	940 x 998 x 330	940 x 1,210 x 330
Net Weight	Indoor Unit	kg	42.0	46.0
	Outdoor Unit	kg	72.0	85.0
Refrigerant				
Refrigerant	Type		R410A (contains fluorinated greenhouse gases. GWP = 2.088)	
	Factory Charging	kg	3.0	3.5
	Charging Ton equivalent CO ₂	tCO ₂ e	6.26	7.31
	Additional Refrigerant Charging	g/m	50	50
Piping Connections	Liquid Pipe	ø, inch	3/8	3/8
	Gas Pipe	ø, inch	5/8	5/8
Piping Length	Min/Max	m	50	75
Piping Height	Max	m	30	30
Piping Connections	Drain Pipe	ø, mm	VP18	VP18

Accessories


Touch Controller
MWR-SH11N

Advanced Wired Controller
MWR-WG00JN/MWR-WG00KN

Wi-Fi Kit
MIM-H04EN

External Thermostat
MRW-TA

¹ Energy labels as shown are according to EU No 626/2011 (LOT10) label classification 2019, on a scale from D to A+++.

Copyright © 2020 Samsung Electronics Air Conditioner Europe B.V. All rights reserved. Samsung is a registered trademark of Samsung Electronics Co., Ltd. Specifications and designs are subject to change without notice and may include preliminary information. Non-metric weights and measurements are approximate. All data was deemed correct at the time of creation. Samsung is not liable for errors or omissions. Some images may be digitally altered. All brand, product, service names and logos are trademarks and/or registered trademarks of their respective owners and are hereby recognised and acknowledged.

Samsung Electronics Air Conditioner Europe B.V.
 Evert van de Beekstraat 310, 1118 CX Schiphol
 P.O. Box 75810, 1118 ZZ Schiphol
 +31 (0)8 81 41 61 00
 The Netherlands